

Collector²

Relay



Product Overview

Specifications

Input	190 ~ 250V/AC, 3Amp Fused
Output	190 ~ 250V/AC, 600W
Operating Temperature	0 °C ~ 40 °C 10% ~90% RH
Storage Temperature	-10 °C ~ -70 °C 5% ~90% RH
Teach Button	• Silux Control® network • Direct connect • Software teach available
Network	Silux Control® RF proprietary encrypted
RF Range	50m open air & meshing up to 1km
Radio Frequency	868MHZ (Adjustable frequency to meet different country legislations)
Encryption	Silux Control® RF proprietary meshing
Language	English, others coming soon
OS	Android 4.0+, iOS 8.0+, Windows 7+
App Software	Silux Control® can be integrated with other automation features of Silux Control®

The Collector® Relay joins into your existing electrical infrastructure without extra wiring and enables you to switch your low power devices, such as lights, on and off or control devices through schedules and scenes via the Silux Control® app software automatically.

Features:

- Switch LED/incandescent lighting or other similar load devices on/off
- Control schedules & scenes through the Silux Control® IntelliHub®

Note: Can be used without the need of an IntelliHub® by being programmed as direct connect with the Touch Lamina®

Works cooperatively with:		Product dimensions: 38.5 x 92 x 22.5 mm	
----------------------------------	--	---	--